



TECHNIMOUNT
EMS[®]

XTENSION PRO[®] ASSISTANT - CCT

iNO Configuration

The Xtension Pro Assistant-CCT iNO is designed to secure multiple medical devices on a stretcher during critical care ground transport. The robust mobile structure features a gliding system that facilitates lateral patient transfer.

- 3 Standard Surface Bases for quick installation and removal of medical devices.
- Mounts an iNO delivery system or an ECMO device, a monitor/defibrillator, a ventilator and 6-8 infusion pumps.
- Type D Cylinder harness and holder.
- Tested in compliance with SAE J3043 & AMD-028.



XTENSION PRO[®] ASSISTANT - CCT

Technical Specifications

| | |
|--------------------------------------|---|
| Product Name | Xtension Pro Assistant-CCT/iNO |
| Description | Mounting system for ground critical care transport on a Stryker [®] Power-PRO [™] XT stretcher |
| Product Code | 1713-10-PFXT-BX2-XX (Baxter) 1713-10-PFXT-BB2-XX (B.Braun) 1713-10-PFXT-SA2-XX (Sapphire) |
| Operating Environment | EMS/CCT (ground) |
| Compliance | Tested in compliance with SAE J3043 and AMD-028 |
| Compatible Stretcher | Stryker [®] Power-PRO [™] XT |
| Compatible Mounting System | Bracket Pro Serie [®] 25-Flex Bracket Pro Serie [®] 25-HD Bracket Pro Serie [®] 25-WOB Bracket Pro Serie [®] 27 Bracket Pro Serie [®] 60-GR Bracket Pro Serie [®] 111 Bracket Pro Serie [®] 112 Bracket Pro Serie [®] 280 |
| Compatible Medical Device | ZOLL X Series [®] ZOLL Zenix [®] Hamilton-T1 [®] Air Liquide SoKINOX [™] Getinge Cardiohelp [™] Ventec Life VOCSN [™] B. Braun Infusomat [®] Space [®] Baxter Spectrum IQ [™] Eitan Medical Sapphire [™] D-Type cylinder |
| Dimensions (W X D X H) | <ul style="list-style-type: none">- 1713-10-PFXT-BX2-XX: 63.86 cm x 68.88 cm x 74.22 cm (25.14 in x 27.12 in x 29.21 in)- 1713-10-PFXT-BB2-XX: 63.86 cm x 71.65 cm x 74.22 cm (25.14 in x 28.21 in x 29.21 in)- 1713-10-PFXT-SA2-XX: 63.86 cm x 63.12 cm x 74.22 cm (25.14 in x 24.85 in x 29.21 in) |
| Weight | 1713-10-PFXT-BX2-XX: 37.93 kg (83.592 lb) 1713-10-PFXT-BB2-XX: 39.30 kg (86.654 lb) 1713-10-PFXT-SA2-XX: 37.50 kg (82.676 lb) |
| Composition | Aluminum, Stainless Steel, Acetal |
| Total Safe Working Load (SWL) | 1713-10-PFXT-BX2-XX: 46.27 kg (102.008 lb) 1713-10-PFXT-BB2-XX: 44.88 kg (98.946 lb) 1713-10-PFXT-SA2-XX: 46.68 kg (102.924 lb) |
| Operating Temperature | - 35° C to 45° C (- 31° F to 113° F) |
| Options | Integrated Power Bar (1-2) |

technimount.com

Bracket Pro Serie, Technimount EMS are Registered Trademarks of Technologies CGC Inc.

All medical device product and company names are trademarks[™] or registered[®] trademarks of their respective holders.

© 2026 Technimount EMS Holding Inc. - All Rights Reserved - Printed in Canada

FL-CCT-INO-202604EN-01