

Technimount System Inc. Administration 4401, de Guinecourt st. Quebec City (Quebec) G1Y 3S9 Telephone : 1-581-989-9820 Fax : 1-855-339-6351

info@technimount.ca www.technimount.com

Bracket Pro Serie 25[™] Mounting system for Monitor / Defibrillator ZOLL X Serie

Characteristics

- Lightweight
- Compact size
- Swivel base 360° with locking system
- Quick Release and reattachment
- Safe and Easy
- immediate access
- Match with other mount system from us.

Application of use

- Crash cart
- Ambulance
- EMS Vehicles
- Helicopter
- Aircraft
- Stretcher/cot
- Military Vehicles

Advantages

- Minimum space for installation
- No vertical release
- Latex free
- Resist to the biological fluid
- Insensitive to rust
- 1 year full warranty





Our locking systems "*Bracket Pro Serie 25*TM "are designed for fast access to the unit, with little effort in times of emergency uses. The features of this support are the very small size (weight) and the method of locking it (*no vertical movement; less potential injury overtime, and minimum space for installation*).

To spare the expenses of costly repair or replacement of the equipment, and medical care and possible legal redress for injury, consider outfitting your EMS vehicle or crash cart with a deployment system for monitor and/or defibrillator.

The mounting systems offer different configurations for most external defibrillators on the market. They have many characteristics, more specifically to rotate up to 360 degrees with a locking system. The deployment of the unit is almost instantaniously and the system locked the unit after use and resist to an impact of many times the «G» Force.

Technimount System Inc sells, develops and commercialize deployment system for medical equipment that can be fit with different brand names of defibrillator, in hospital, EMS, or military environment.



FY 2017-01 Version 8.4 English

For use with model **ZOLL** Defibrillator « X Series[™] »

TECHNICAL SPECIFICATIONS

Product name:	Bracket Pro Serie 25
Compatibility model:	Monitor – Defibrillator ZOLL « X Series » or " Propaq MD"
Environment of use:	EMS / Hospital – Clinic – Biomed shop – Military hospital -
Material:	Base: Aluminum high density w/ anodize process Device section: Aluminum high density w/ anodize process
Temperature of use:	- 35° C @ 45° C (Direct conduction)
Impact Resistance ¹ :	(30«G») Plus 10% safety factor (On certified hook)
Nbr of installation point:	4 points on surface base: 4 points on device mount
Dimensions (both parts assy- overall):	13-1/4" Width X 9-3/8" Depth X 1-1/4" Thickness (inch.)
Rotation:	360° degrees with locking system (small base) 15° degrees both sides with locking system (Long base)
Features:	 With or without Carry case protector Compatible with Technimount cot system Compatible with extended surface base Free access to all connectors and accessories (top)
Weight:	Total (2 parts) 2.9 lbs - device section: 1.35 lbs. –
Options:	Extended surface base (longer) Spacer (height extension mount 3/8", ½", ¾") Table top converter (surface base cover for work space)
Locking mechanism resistance:	Over than 20 000 movements without any fatigue
Part number ² :	100-00-XZ "Bracket Pro Serie 25" Complete
Part number :	100-10-XZ "Bracket Pro Serie 25" Disc only upper part
Part number :	100-20-UN "Bracket Pro Serie 25" Base part only



Installation suggested

¹ *Technimount System Inc* works to meet and exceed all legal requirements in the deployment system for EMS vehicles, according to the Provincial & Federal Government regulations, it may not meet your local requirements, please contact your administrator.

² Part number must be confirmed prior sending purchase order. Technimount System inc reserves the right to make changes on the product, documents and technical specifications without notice and responsibilities. DOCUMENTS PRINTED IN CANADA CGC Technologies – Division of Medical equipment & accessories – Registered brand 2013