

Flexytrans-connect™ 501

Flexible connexion for Medical Gaz for Ambulance installation

Technical Specifications

Product name	Flexytrans-connect™ 501
Product identification	2 x O ₂ OUTLETS SYSTEM (2 ECC), EX
Environment of use	OEM Ambulance builder for patient compartment for medical gas
Material	Brass - Chrome / Accuflex 109
Temperature of use	-4° to 65° C (25° to 150° F)
Length connection available	Minimum 24"', up to request
Installation points	2 points per connector - model depending - option available
Dimensions	Dia. 1/4"
Operating pressure	100 Psi
Flow rate	170 CFH
Maximal Binding array	3 inches radius
Weight	4 lbs.
Connector type	Diss O ₂
Compatible connection to	Diss O ₂
Options available	For valves and quick-connect possibilities, contact us for confirmation
Spare parts available	On demand, contact us
Certification testing ¹	Clean for Oxygen services as per CGA G-4.1 NFPA99 5.1.12.2.6.3
Part number²	FTC-3100-0501



¹ Those specifications are designed for civilian ambulance for EMS; please refer to your administrator for certifications.

² Part number must be confirmed prior sending purchase order.

Technimount System Inc reserves the right to make changes on the products, documents and technical specifications without notices and responsibilities.

TECHNIMOUNT

SYSTEM

Technimount System
Administration
445 Papin Street- Office 103
Quebec City (Quebec), Canada
G1P 3T8
Telephone: +1-581-998-9820
Fax: 1-855-339-6351

info@technimount.com

www.technimount.com

Connection configuration:

