



BRACKET PRO SERIE® 25 FLEX

MOUNTING SYSTEM FOR ZOLL® X SERIES® MONITOR/DFFIBRILL ATOR

SAFETY AND FLEXIBILITY WHERE IT **MATTERS MOST**

The Bracket Pro Serie® 25 Flex is designed for intensive use in tough EMS environments. It provides fast and easy access to the ZOLL® X Series® monitor/defibrillator.

The Bracket Pro Serie® 25 Flex complies with the highest industry safety standards for transport of medical equipment, SAE J3043.

At Technimount, we understand that clients need solutions that they can count on. We design and develop the best solutions for quality, flexibility and safety in all of our mounting systems through collaborative partnerships with our customers.











BRACKET PRO SERIE® 25 FLEX

POTENTIAL CONFIGURATIONS



TECHNICAL SPECIFICATIONS

Product Name	Bracket Pro Serie® 25 Flex
Compatibility of Medical Device	ZOLL® X Series® Monitor/Defibrillator
Environment of Usage	EMS/CCT (Ground & Flight) – Hospital/Clinic, Military
Device Section Material	Bracket - UV Stabilized ABS Plastic Top Plate - High-Density Aluminum with Black-Anodized Finish
Bottom Disc Section Material	Aluminum with Stainless Steel Insert and Peek Cushions
Temperature of Usage	- 35° C @ 45° C (Direct Conduction)
Impact Resistance - Ground - USA	SAE J3043 (30 G) Plus 10% Safety Factor (in process)
Impact Resistance - Flight	Designed to comply with FAA – FAR -DOT 27.561 & DOT 27.562 up to 20G
Medical Device Retaining System	Device Retained on Main Assembly with 3 blocks: 1 lateral block and 2 side blocks installed into the medical device
Retaining System	1 Standard Bottom Disc
Transportation Compatibility System	 Compatible with Technimount's Standard Surface Base Compatible with Technimount's Stretcher Safety Arm System For Stryker Cots (PowerPro - XT and Mx-Pro) Compatible with the Floor Mount Platform (Flight) Compatible with Wall Mount System (Standard Base System)
Features	 Robust Mounting Solution for EMS/CCT/ALS Transport Access to all Connectors and Accessories Flight and Ground Compatibility Multiple Configuration Options for Transport
Physical Overall Dimensions	Length 13.2 in Height 1.63 in, Depth 8.0 in
Weight (Bracket Only)	Bracket Only - 1.9 lbs Bracket with Device - 13.6 lbs
Part Number	Bracket only - 100-13-XZ-FX







YOUR SAFETY IS OUR PRIORITY



FEATURES

- Made from high-density aluminum and durable UV Stabilized ABS Plastic
- Resistant to biological fluids and Quaternary-type disinfectants
- Universal standard bottom disc for installation on Technimount's Standard Surface Base systems
- Designed with a positive curve so bracket becomes level with the weight of the medical device to protect the standard bottom disc
- Molded feet eliminate the need for replacement and protect the bracket and the medical device when placed on the ground

BENEFITS

- Bracket is extremely durable and abrasive resistant, designed for tough EMS applications
- Combination of bracket and medical device remain lightweight and flexible
- Quick installation and removal of bracket from Technimount's mounting systems
- Access to medical device from all angles (360°rotation on Technimount's Standard Surface Base)
- Certified mounting system that complies with the highest industry standards and regulations, SAE J3043
- Reduces risks of damage to the equipment and ensures the safety of patients and crew during EMS and Critical Care transport



SAFETY AND FLEXIBILITY WHERE IT MATTERS MOST

