



TECHNIMOUNT
EMS™



BRACKET PRO SERIE® 25 - HD

MOUNTING SYSTEM FOR ZOLL® X SERIES® MONITOR/DEFIBRILLATOR

SAFETY AND FLEXIBILITY WHERE IT MATTERS MOST

The Bracket Pro Serie 25 - Heavy Duty (HD) is designed to give fast and easy access to the ZOLL X Series monitor/defibrillator. This rugged solution was designed for tougher environments and more challenging emergency situations.

The Bracket Pro Serie 25 - HD is tested in compliance with SAE J3043, the highest industry safety standards for the transport of medical equipment.

At Technimount EMS, we understand that EMS and Critical Care Transport teams need solutions that they can rely on. We design and develop quality mounting systems which are safe and flexible, allowing you to concentrate on what matters most - patient care.

BRACKET PRO SERIE® 25 - HD

Standard Surface Base



Safety Arm System



Wall Mount Pro

TECHNICAL SPECIFICATIONS

Product Name	Bracket Pro Serie® 25 - Heavy Duty
Description	Single disc, robust bracket mounting system to secure the ZOLL® X Series® on surfaces and cots/stretchers in emergency vehicles
Part Number	<ul style="list-style-type: none">- 100-12-XZ-HD – Bracket Pro Serie 25® - HD- 100-20-UN – Standard Surface Base
Features	<ul style="list-style-type: none">- Designed for monitor with or without carrying case protector- 360° rotation on Technimount's Standard Surface Base- Free access to all connectors and accessories (top & back pouches)
Operating Environment	<ul style="list-style-type: none">- EMS/CCT (Ground)- Hospital/Clinic, Military
Compliance	Tested in compliance with: <ul style="list-style-type: none">- SAE J3043
Compatible Mounting System	Compatible with: <ul style="list-style-type: none">- Standard Surface Base- Safety Arm System for Stryker Cots (PowerPro-XT and MX-PRO)- Wall Mount Pro- Other compatible systems available
Dimensions (W x D x H)	13.25 in. x 8.5 in. x 1.25 in. (33.66 cm x 21.6 cm x 3.2 cm)
Weight	1.54 lbs (0.69 kg)
Composition	<ul style="list-style-type: none">- Main assembly: aluminum 6061-T6, black anodized finish- Standard bottom disc: aluminum 6061-T6 with 304 stainless steel Insert, silver anodized finish
Operating Temperature	- 31° F to 113° F (- 35° C to 45° C)
Installation	Device retained with 3 blocks: 1 rear block and 2 side blocks installed into the medical device
Model & Configuration Options	<ul style="list-style-type: none">- For air transport: Bracket Pro Serie 25® - HD(100-15-XZ-HD-FL)- Contact Technimount EMS for more information or for other options at customerservice@technimount.com.

YOUR SAFETY IS OUR PRIORITY



FEATURES

- ✓ Supports multiple mounting configurations on surfaces, stretchers, and carts.
- ✓ Lightweight, compact bracket that respects the integrity and functionality of the medical device.
- ✓ Long-lasting, integrated feet to place the bracket on a flat surface.
- ✓ Made from highly resistant aluminium with black anodized finish for added durability and corrosion.
- ✓ Tested in compliance with SAE J3043, the highest industry safety standards for the transport of medical devices.

BENEFITS

- + Quick installation and removal of bracket and access to medical device from all angles (360°rotation).
- + No interference with the monitor/defibrillator connectors and wires; access to the device at all times.
- + Provides stability to the device and helps prevent damage to the standard bottom disc.
- + Minimizes the risks of damage or replacement of the equipment.
- + Ensures the safety of patients and personnel during EMS and critical care transport.



SAFETY AND FLEXIBILITY WHERE IT MATTERS MOST

technimount.com