



BRACKET PRO SERIE® 35 - LP

MOUNTING SYSTEM FOR THE STRYKER LIFEPAK® 15 MONITOR/DEFIBRILLATOR

SAFETY AND FLEXIBILITY WHERE IT MATTERS MOST

The Bracket Pro Serie 35 - LP is designed for intensive use in tough EMS environments. It secures the LIFEPAK 15 on emergency vehicle surfaces, stretchers, and floors.

The Bracket Pro Serie 35 - LP is tested in compliance with SAE J3043, the highest industry safety standards for EMS and CCT transport.

At Technimount EMS, we understand that EMS and Critical Care Transport teams need solutions that they can rely on. We design and develop quality mounting systems which are safe and flexible, allowing you to concentrate on what matters most – patient care.

BRACKET PRO SERIE® 35 - LP

POTENTIAL CONFIGURATIONS

Standard Surface Base

Safety Arm System™



TECHNICAL SPECIFICATIONS

| Product Name | Bracket Pro Serie® 35 - LP |
|-------------------------------|---|
| Description | The Bracket Pro Serie® 35 - LP is designed to secure the Stryker® LIFEPAK® 15 monitor/ defibrillator during emergency medical services and critical care transport |
| Part Number | 210-12-PC15-LP (Bracket Pro Serie[®] 35 - LP) 100-20-UN (Standard Surface Base) |
| Features | Compatible with multiple mounting configurations on surfaces, stretchers, and cots Compatible with or without bags Access to top, side and rear accessory bags, screen, connectors and monitor/ defibrillator accessories |
| Operating Environment | EMS/CCT (Ground), Military |
| Compliance | – Tested in compliance with SAE J3043 |
| Compatible Mounting System | Standard Surface Base Safety Arm System[™] Xtension Pro[™] Assistant CCT Other compatible systems available |
| Dimensions (W x D x H) | 15.3 in. x 10.5 in. x 12.8 in. (38.1 cm x 25.4 cm x 30.4 cm) |
| Weight | 5.1 lb (2.27 kg) |
| Composition | Bracket Pro Serie[®] 35 - LP: aluminum 6061-T6, black anodized finish Standard bottom disc: aluminum 6061-T6, 304 stainless steel inserts Retaining frame: stainless steel with black thermoplastic coating Feet: Acetal Bumpers: SBR rubber |
| Safe Woriking Load (SWL) | 26 lbs (11.8 kg) |
| Operating Temperature | - 31° F to 113° F (- 35° C to 45° C) |
| Installation | Monitor/defibrillator secured in mounting system by retaining frame screwed on the bottom plate |
| Model & Configuration Options | For air transport: Bracket Pro Serie[®] 35 - LP (210-14-PC15-LP-FL) Contact Customer Service at <u>customerservice@technimount.com</u> |
| | |

* Medical device manufacturer and product names are Trademarks[™] or Registered Trademarks[®] of their respective holders. Technimount does not have a commercial relationship with these manufacturers.

YOUR SAFETY IS OUR PRIORITY



FEATURES

- Secures the LIFEPAK 15 with its side, rear and top pouches.
- Retaining frame that allows for easy medical device installation while keeping a low profile design.
- Tailored design adapts to the medical device's outline.
- Front handle on the bottom of the bracket and sturdy integrated feet.
- > Environment of usage: EMS/CCT (Ground), military.
- Designed to comply with SAE J3043.

BENEFITS

- Securely transport the LIFEPAK 15 during EMS/Critical Care Transport on stretchers, surfaces and floors.
- Simple device installation and removal with the bracket from the Standard Surface Base.
- No interference with the medical device printer, cables, and connections.
- Increased ergonomics and maneuverability due to its front handle.
- Reduces the risk of injury to patients and crews during patient transport.
- Innovative design distributes impact loads evenly on the bracket.

SAFETY AND FLEXIBILITY WHERE IT MATTERS MOST



technimount.com

Bracket Pro Serie, Technimount EMS are Registered Trademarks of Technologies CGC Inc. LIFEPAK 15 is a trademark of Stryker Physio-Control.

© 2023 Technimount E.M.S. Holding Inc. – All Rights Reserved - Printed in Canada TS-BP35LP-202304EN-02